

Rec'd PCT/PTO 25 FEB 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

10/525656

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2004 (06.05.2004)

PCT

(10) International Publication Number
WO 2004/037480 A1

(51) International Patent Classification:
B25B 23/12, 15/06

B23P 19/06,

(72) Inventor; and

(75) Inventor/Applicant (for US only): SASAKI, Shuichi
[JP/JP]; c/o Honda Motor Co., Ltd., Saitama Plant, 10-1,
Shinsayama 1-chome, Sayama-shi, Saitama 350-1392 (JP).

(21) International Application Number:

PCT/JP2003/013472

(22) International Filing Date: 22 October 2003 (22.10.2003)

(74) Agents: SHIMODA, Yo-ichiro et al.; Meisan Tameike
Bldg., 1-12, Akasaka 1-chome, Minato-Ku, Tokyo 107-
0052 (JP).

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2002-311948

25 October 2002 (25.10.2002) JP


Published:

— with international search report

(71) Applicant (for all designated States except US): HONDA
MOTOR CO., LTD. [JP/JP]; 1-1, Minami-Aoyama
2-chome, Minato-ku, Tokyo 107-8556 (JP).

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS FOR TIGHTENING THREADED MEMBER



(57) Abstract: An apparatus (10) for tightening a hexagon head bolt (13) includes a vertically movable automatic robot arm (16), a screwing mechanism (18) having a rotational part (19), a shaft member (20) mounted to the rotational part, a socket portion (21) mounted to the shaft member for receiving therein a head (14) of the bolt, and a retention means (22) for retaining the head received in the socket portion or retaining the head released from the socket portion. When the arm moves vertically with the head received in the socket portion, the rotational part is rotated along with the shaft member and the socket portion to screw the bolt into a threaded aperture (12) of a crankcase (11) of an engine.

WO 2004/037480 A1